

STANCE



SPECS

QUADRO	
TAMANHOS	S, M, L, XL
CORES	T/K
QUADRO	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution
FORQUILHA	Giant STL 34 dual air, 140mm, 15x110, thru-axle
AMORTECEDORES	GU: Fox Rhythm, rebound, 210x52.5 Other GSCs: Crest FloTrac Elite TR, 2-position lockout, 210x52.5
COMPONENTES	
GUIADOR	Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm rise/760mm, M:35mm rise/760mm, L:35mm rise 800mm, XL:35mm rise 800mm
PUNHOS	Giant Tactal, lock on
AVANÇO	Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm
ESPIGÃO DE SELIM	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELIM	Giant Contact Ergo Trail
TRANSMISSÃO	
MANETES	Shimano CUES SL-6000, 1x10
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	Shimano CUES RD-U6000, Shadow +
TRAVÕES	Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm
MANÍPULOS DOS TRAVÕES	Tektro HD-M5141
CASSETE	Shimano CUES, CS-LG300, 11x48
CORRENTE	KMC X-11
CONJUNTO PEDALEIRO	Shimano CUES FC-U6000, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
MOVIMENTO CENTRAL	Shimano, threaded

RODAS	
AROS	Giant AM30 alloy rim
CUBOS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body
RAIOS	stainless, 28, J-bend
PNEUS	[F] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 32t

Preço: 1 799,00 €

GEOMETRIA

QUADRO	XS	S	M	L	XL
Comprimento do tubo do assento (mm)	380	400	425	450	475
Seat Post Insertion Depth (mm)	250	270	290	320	390
Ângulo do tubo do assento	77,0°	76,5°	76,5°	76,5°	76,5°
Comprimento do tubo superior (mm)	547	567	600	627	659
Comprimento do tubo principal (mm)	95	100	110	120	130
Ângulo do tubo principal	65,0°	65,0°	65,0°	65,0°	65,0°
Garfo ancinho (mm)	44	44	44	44	44
Trilha (mm)	129	129	129	129	129
distância entre eixos (mm)	1158	1176	1210	1239	1274
Comprimento Chain Stay (mm)	440	442	442	442	442
Suporte inferior (mm)	25	40	40	40	40
Pilha (mm)	613	615	624	633	642
Alcançar (mm)	405	420	450	475	505
Altura do standover (mm)	758	754	748	744	738
Largura do guidão (mm)	760	760	760	780	780
Comprimento da haste (mm)	40	40	40	40	40
Comprimento da Manivela (mm)	165	165	165	165	165
Tamanho da roda	29" [F] 27.5" [R]	29"	29"	29"	29"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.